

# New Spindle Moulder (Shaper)

With Digital Control Elevation and Variable Speed Spindle

## Special Features:

- Precision spindle of different sizes to choose from: 1-1/4", 30 mm., 35 mm., 40 mm. and 50 mm.
- Four spindle speeds: 3,000/4,500/6,000 and 8,000 RPM.
- Heavy-duty design with modern appearance.
- All cast-iron table and guide fence with precision grinding capabilities.
- Standard model is the CMP-6. The CMP-6HP features electronic spindle digital readout and a 'stand-up'/removable control panel. The CMP-6HPD has the same specifications as the CMP-6HP and also includes inverter spindle control for variable speed requirements (2,500 ~ 10,000 RPM).
- 'CE' standard model available upon request. Extension table & front support is available.



**CMP-6**



**CMP-6HPD**



## Digital Control Panel

'Stand-up'/removable control with electronic, LED digital readout for setting spindle and inverter spindle control for variable RPM speed.

## SPECIFICATIONS

MODEL	CMP-6	CMP-6HP	CMP-6HPD
Spindle Speed	3,000 / 4,500 / 6,000 / 8,000 R.P.M.		
Spindle Size	1-1/4" or ø30 mm or ø35 mm or ø40 mm or ø50 mm		
Table Area (L x W)	1,200 x 890 mm	1,200 x 890 mm	1,200 x 890 mm
Spindle Rise and Fall	125 mm	125 mm	125 mm
Table Height	870 mm	870 mm	870 mm
Packing Size (L x W x H)	1,240 x 1,040 x 1,100 mm	1,270 x 1,150 x 1,720 mm	1,270 x 1,150 x 1,720 mm
Net Weight	530 kgs	580 kgs	600 kgs
Gross Weight	630 kgs	700 kgs	720 kgs

# HOLYTEK

**HOLYTEK INDUSTRIAL CORP.**

9F-I, NO. 400, SEC. 1, CHANG PING RD., TAICHUNG, TAIWAN, R.O.C.

TEL: 886-4-2245-2818 (REP.) FAX: 886-4-2243-6928

E-mail: holytek@ms13.hinet.net

http://www.holytek.com.tw